



Label Specification



710HA Plain DE 8.2 QRL



2000 Good Labels Per Tray

Product Description	710HA Plain DE 8.2 QRL
Part No:	7232717
Label Dimensions (WxH):	34x39 mm / 1.34"x1.54"
Distance between labels (D):	3.2 mm / 0.13"
Linear Width (L):	36 mm / 1.42"
External Roll Diameter (ER):	Ø 90 mm / 3.54"
Inner Core Diameter (IC):	Ø 25.4 mm / 1.0"
Face Sheet:	White Coated Paper
Adhesive:	All Purpose Grade
Labels per roll:	500
Labels per tray:	2000 (4 rolls Shrink Wrap)
Labels per case:	20,000 (40 rolls)
Approx. Weight roll:	0.21 kg / 0.46 lbs.
Approx. Weight case:	8.4 kg / 18.52 lbs.
Frequency (MHz) ± 5%:	8.2 MHz
Electrostatic Discharge Tolerance (ESD):	1.5kv
*Minimum Order Quantity (MOQ):	1 Tray / 2000 labels

Storage conditions: Keep dry but do not expose to direct sunlight • Recommended storage temperature: 18 to 29°C Maximum temperature should not exceed 43°C • Maximum shelf life of RF labels when stored in recommended conditions in 2 years**

• Cases should never be stacked more than 5 high.

* Unless otherwise specified in contractual conditions

** RF circuits have no expiry date; however the adhesive has a useful working life of 2 years from the date of manufacture

For any questions regarding this or any other labelling process contact your local Checkpoint representative.

All rights reserved © Checkpoint Systems Inc. Thorofare, USA 2019
All information and illustrations are intellectual property of Checkpoint Systems, Inc.
Any copying, reprinting, manipulating or publishing in part or in whole is strictly prohibited.
Last Modified: 05/02/2019

checkpointsystems.com