
## **Label Specification**



4115 RF Metal™







Product description:	4115 RF Metal TT BL 0.5KR/76
Part number:	10152250
Label Dimensions (W x H x T)	41mm x 14mm x 0.8mm (1.61" x 0.55" x 0.03")
Distance between labels (D):	13mm (0.51")
Liner Width (L):	Ø 43 mm (1.69")
External Roll Diameter (ER):	Ø 142mm (5.59")
Inner Core Diameter (IC):	Ø 76.2mm (3")
Face Sheet:	White TT paper
Adhesive:	General Purpose PSA
Labels per roll:	500 Pcs
Labels per case:	10,000Pcs
Approx. Weight roll:	0.4kg/0.88lbs.
Approx. Weight case:	9.5kg/20.94lbs.
Frequency (MHz):	8.2MHz +/- 5%

Storage conditions: Keep dry but do not expose to direct sunlight  $\cdot$  Recommended storage temperature: 18 to 29°C. Maximum temperature should not exceed 43°C  $\cdot$  Maximum shelf life of RF labels when stored in recommended conditions is 2 years\*  $\cdot$ 

Cases should never be stacked more than 5 high.

\*RF circuits have no expiry date; however the adhesive has a useful working life of 2 years from the date of manufacture. For any questions regarding this or any other labelling process contact your local Checkpoint representative.

All rights reserved © Checkpoint Systems Inc. Thorofare, USA 2022 All information and illustrations are intellectual property of Checkpoint Systems, Inc. Any copying, reprinting, manipulating or publishing in part or in whole is strictly prohibited.

Last Modified: 10/05/2022

