

SUNMI L2K



- 2GB RAM+16GB ROM
- Increased expansion options support multiple accessories
- The industry-grade touch screen comes with a glove mode option
- Compatible with Honeywell/Zerba 1D and 2D barcode scanners
- Built-in small battery allows for replacement of the main battery without needing to turn off the mobile computer
- With this UHF trigger handle, SUNMI L2K can enhance your work efficiency by enabling the reading of multiple RFID tags.



1.5W
loudspeaker



IP65
rating



1.5M
drop proof



SUNMI L2K
Charging Base (optional)

SUNMI L2K
UHF Trigger Handle (optional)

SUNMI L2K Technical specifications

OS Android 7.1 SUNMI OS	CPU Qualcomm quad-core 1.4GHz CPU	Memory 16GB ROM+2GB RAM	Display 4" WVGA 800×480,IPS Multi touch, Support glove mode	Adapter Input:Type-C Output:DC 5V/2A
Wi-Fi 2.4G/5G Support IEEE 802.11 a/b/ g/n	Bluetooth Support BLE Support Bluetooth 2.1/ 3.0/4.2	Voice and Audio 1.5W Two mic	Port 1x Type-C USB Support OTG Support pogo pin	Key Power button Volume up/down Scan button 20 physical keys
Battery Removable polymer Lithium battery 3.8V/5000mAh	Communication 2G/3G/4G	1D/2D Scanner Zebra 2D scanner Honeywell(Optional)	Camera Rear: 13MP autofocus Front: 2MP fixedfocus	NFC ISO 14443 Type A/B FeliCa and ISO 15693 cards
GPS Support AGPS Support GPS/Glonass/Beidou	SIM Card Slot SIMx1 PSAMx1 Support 1.8V/3.0V	Size 159.4*73*19mm	Environment Operating temperature: -20°C~55°C Storage temperature: -40°C~70°C Sealing: IP65 Drop Specification: 1.5m	

Optional



Trigger Handle
Support barcode reading



UHF Trigger Handle
Support RFID tag
reading and writing



Charging Base
Support L2K and UHF charging

SUNMI L2K UHF Trigger Handle Technical specifications

RFID Engine Impinj Indy R2000	Fastest Read Rate >200 tags/sec	Longest Read Range >10m	Antenna Circularly polarized (4dBi)	Battery 3.6V/3350mAh
Protocols & Standards EPC Global UHF Class 1 Gen 2/ ISO 18000-6C/ ISO 18000-6B	Frequency Range Chinese mainland 920~925MHz American standard 902~928 MHz European standard 865~868 MHz	Environment Operating temperature: -10°C~50°C Storage temperature: -40°C~70°C Sealing: IP65 Drop Specification: 1.5m		

Note:

1. To charge, a SUNMI L2K charging base is needed. 2. Read rate and range depend on actual environments.
3. Real memory will be reduced due to a number of factors, and there are differences. Operating system also occupy part of memory.
4. Actual product specifications when sold take precedence over what may be listed at this catalogue; Any changes may be made without prior notification.